



# I-Series for Linux

All-in-One Touchscreen



Linux Debian 10



Choose 10-, 15-  
or 22-inch sizes



Enterprise-Grade  
Support

## Product Overview

One of our most popular product lines ever, the I-Series has been used across the globe for everything from self-service, point-of-sale and price checkers to industrial controls and visitor management. Available in 10-, 15- and 22-inch sizes, Elo's I-Series delivers a powerful, commercial-grade interactive platform complete with a Full HD 10-touch display, Linux Debian 10 OS and enhanced CPU performance a Rockchip processor.

With decades of development and customizations made to support global enterprise customers, Elo's Linux-based platform offers Linux device drivers, uniform SDKs, a constantly growing set of tools and an expansive lineup across sizes and form factors.

Available in 10", 15" or 22" widescreen sizes with an edge-to-edge glass PCAP touchscreen

Elo's Linux-based platform offers device drivers, uniform SDKs, and a constantly growing set of tools

Modular design with flexible mounting

## I-Series for Linux AiO Touchscreen

Specifications	10-inch model	15-inch model	22-inch model
Diagonal Size	10.1" (256.54mm)	15.6" (396.24mm)	21.5" (546.10mm)
Operating System	Linux Debian 10		
Processor	Rockchip RK3399		
Memory	4GB		
Storage	32GB		
I/O Ports	1x USB 3.0 support (900mA), Type C USB output, Micro SD slot, GPIO, Ethernet 1x LAN (Gigabit), DC in 4x micro-USB 2.0 Elo Edge Connect ports (Support for 1.2A on one port and 500mA for the remaining three ports)		
Wireless	802.11a/b/g/n/ac + Bluetooth 5.0		
Webcam	5MP, Max Resolution: 1920x1080 30fps, Auto Focus		
Speakers	2x 2W		
Audio	1x built-in Analog Microphone		
Active Display Area	8.54" x 5.34" / 217 mm x 136 mm	13.55" x 7.62" / 344 mm x 194 mm	18.74" x 10.54" / 476 mm x 268 mm
Resolution	1280 x 800 @ 60Hz	1920 x 1080 @ 60Hz	
Touch Technology	TouchPro® PCAP (Projected Capacitive) - up to 10 touches		
Aspect Ratio	16:10	16:9	
Number of Colors	8-bit (16.7M)		
Brightness	LCD Panel: 300 nits; PCAP: 250 nits	LCD Panel: 250 nits; PCAP: 215 nits	
Response Time	25 ms		5 ms
Viewing Angle	Horizontal: ±85° or 170° total / Vertical: ±85° or 170° total	Horizontal: ±80° or 160° total / Vertical: ±80° or 160° total	Horizontal: ±85° or 170° total / Vertical: ±80° or 160° total
Contrast Ratio	800:1	700:1	1000:1
Power	AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz		
Power Consumption	On: 5.89W Off: 0.32W Sleep: 3.33W	On: 8.91W Off: 0.37W Sleep: 3.71W	On: 14.49W Off: 0.32W Sleep: 3.20W
Power Over Ethernet	Supported via Elo PoE Device PN: E413396 - Reference the I-Series user guide for details.		
Dimensions (W x D x H)	9.96" x 6.65" x 0.87" / 252.9 mm x 169.0 mm x 22.1 mm	15.34" x 9.83" x 0.88" / 389.7 mm x 249.7 mm x 22.3 mm	20.66" x 12.79" x 1.17" / 524.8 mm x 324.8 mm x 29.7 mm
Shipping Dimensions	12.4" x 5.5" x 9.0" / 315 mm x 140 mm x 228 mm	18.3" x 6.3" x 13.0" / 465 mm x 160 mm x 330 mm	23.6" x 6.6" x 16.0" / 600 mm x 168 mm x 406 mm
Weight	1.8 lbs / 0.8 kg	3.5 lbs / 1.6 kg	9.5 lbs / 4.3 kg
Shipping Weight	4.9 lbs / 2.2 kg	7.2 lbs / 3.3 kg	16.1 lbs / 7.3 kg
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)		
Humidity	Operating: 20%-80%; Storage: 5%-95%		
Mounting Options	VESA 75mm	VESA 75mm and 100mm	
Warranty	2 years standard		
Extended Warranty	3 year - Elo P/N: E819394; 4 year - Elo P/N: E819598; 5 year - Elo P/N: E819795 3 year + ADP - Elo P/N: E130329; 4 year + ADP - Elo P/N: E130530; 5 year + ADP - Elo P/N: E130719 2 year + AUR - Elo P/N: E819985; 3 year + AUR - Elo P/N: E820186; 4 year + AUR - Elo P/N: E820388; 5 year + AUR - Elo P/N: E820582 2 year + AUR + ADP - Elo P/N: E131490; 3 year + AUR + ADP - Elo P/N: E131674; 4 year + AUR + ADP - Elo P/N: E131859; 5 year + AUR + ADP - Elo P/N: E132053		
Regulatory Approvals	UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia); ANATEL (Brazil)		
What's in the Box	I-Series, NA Power Cable, EU Power Cable, 1x Power Brick (E153026), Quick Install Guide, Screws for cable cover door (located in the power/Ethernet bay)		

## Ordering Information

Part Number	Size	Processor	Color	Memory	Storage
E143205	10-inch	Rockchip RK3399	Black	4GB	32GB
E131747	15-inch	Rockchip RK3399	Black		
E143391	22-inch	Rockchip RK3399	Black		

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2023 Elo Touch Solutions, Inc. All rights reserved. 23053AES00173

