



I-Series 2 with Intel®

All-in-One Interactive Display



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

Elo's I-Series delivers commercial-grade computing with the capabilities, security and enterprise infrastructure of a powerful, Intel-based platform—all in a sleek, yet durable fixed tablet form factor. For added flexibility, the I-Series offers models with no OS—all pretested with Linux SuSE, Ubuntu and Red Hat operating systems—allowing businesses to get the solution best suited for them.

Built on a modular platform and available with either 15-inch or 22-inch interactive displays, the I-Series 2 with Intel can be found in installations across the globe, from in-store interaction and point-of-sale to self-service, hospitality and corporate office environments. The uses are virtually unlimited.

Available in 15" and 22" widescreen sizes with high-performance computing and sleek edge-to-edge glass PCAP (10 touch) touchscreen

Elo Edge Connect™ compatibility - EMV, MSR, barcode scanner, fingerprint reader and customer-facing display

Modular design with flexible mounting in portrait, landscape and table-top orientation

15" I-Series 2 with Intel® AiO Interactive Display

| Model | i2 Models | i3 Models | i5 Models |
|---------------------------------------|---|---|---|
| Enclosure Color | Black | | |
| Display | 15.6" / 395 mm diagonal, active matrix TFT LED LCD | | |
| Aspect Ratio | 16:9 (standard) | | |
| Active Display Area (W x H) | 13.55" x 7.62" / 344.2 mm x 193.5 mm | | |
| Native (optimal) Resolution | 1920 x 1080 @ 60Hz | | |
| Touch Technologies | TouchPro® PCAP | | |
| Processor | Intel® Celeron® J4125 Processor (4M Cache, up to 2.7 GHz) | Intel Core i3-9100TE Processor (6M Smart Cache, up to 3.20 GHz by Intel Turbo Boost Technology 2.0) | Intel Core i5-9500TE Processor (9M Smart Cache, up to 3.60 GHz by Intel Turbo Boost Technology 2.0) Intel vPro™ Support |
| Chipset | N/A | Intel H310 Express | Intel Q370 Express |
| Graphics | Intel UHD Graphics 600 | Intel UHD Graphics 630 | |
| BIOS | AMI | | |
| Memory (RAM) | 4GB 2666MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 8GB on 2 slots) | 8GB 2666MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 32GB on 2 slots) | |
| Storage | 128GB M.2 SATA SSD 72 TBW | | |
| Operating Systems | No OS, Windows 10 IoT Enterprise LTSC 64-bit, Optional Windows 10 Professional 64-bit, ChromeOS Flex | | |
| USB Ports | 1 x USB 3.0; 4 x Micro USB for Elo peripherals | | |
| Ethernet Port | 1 x LAN RJ45 (Gigabit) | | |
| Wireless Connectivity | Wi-Fi 802.11 a/b/g/n/ac 2.4GHz and 5GHz and Bluetooth 5.0 | | |
| TPM | TPM 2.0 | | |
| AMT | N/A | Active Management Technology (Intel® AMT 11.0) Support. | |
| Audio | 2 x 2W Internal Speakers; 1 x 3.5mm headset jack | | |
| Colors | 266,144 | | |
| Brightness (typical) | LCD panel: 300 nits; TouchPro PCAP: 270 nits | | |
| Response Time Total (typical) | 25m | | |
| Viewing Angle (typical) | Horizontal: 80°/160° total, Vertical: 80°/160° total | | |
| Contrast Ratio (typical) | 700:1 | | |
| Control Buttons | Power | | |
| Power | External USB-C power supply brick; AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz; Maximum output power: 100W | | |
| Power Consumption | 30W | 67W | 73W |
| Dimensions | 15.6": 15.13" x 9.7" x 1.72" / 384.2 mm x 246.4 mm x 43.8 mm | | |
| Shipping Box Dimensions | 15.6": 18.19" x 8.5" x 13.57" / 462 mm x 216 mm x 346 mm | | |
| Weight | Unpacked: 4.9 lbs / 2.2 kg; Packaged: 9.5 lbs / 4.3 kg | | |
| Temperature | Operating: 0°C to 35°C / 32°F to 95°F; Storage: -20°C to 60°C / -4°F to 140°F | | |
| Humidity (non-condensing) | Operating: 20% to 80%; Storage: 5% to 95% (38.7°C max wet bulb temperature) | | |
| Energy Star Certified | Energy Star 7.1 | | |
| Regulatory approvals and declarations | UL/cUL, FCC, TUV, CE, CB, Mexico NOM, RCM/R-NZ, VCCI, Argentina S-Mark, CCC, UKCA Korea KCC for i5 Models only, Taiwan BSMI for i5 Models only | | |
| Mounting Options | 15.6": 75mm VESA mount | | |
| Real-Time Clock | Replaceable CR2032 lithium battery for clock | | |
| Sealing | Touchscreen sealed to sub-bezel / Touchscreen sealed to LCD | | |
| Warranty | 3-year | | |
| Extended Warranties | 4 year: E819598; 5 year: E819795; 3 year + AUR: E820186; 4 year + AUR: E820388; 5 year + AUR: E820582 | | |
| MTBF | 50,000 hours demonstrated | | |
| Other Features | Serviceable internal components; Kensington lock | | |
| What's in the box | I-Series Touchcomputer, North America power cord, European power cord, Power adapter - 100W, cable cover locking screw, QIG | | |

Ordering Information

| Part Number | Processor | OS | Memory | RAM | Surface Treatment | Touch Interface |
|-------------|-----------|---------------|--------|-----------|-------------------|-----------------|
| E691852 | J4125 | Windows 10 | 4GB | 128GB SSD | Clear | USB |
| E291329 | J4125 | ChromeOS Flex | 4GB | 128GB SSD | Clear | USB |
| E692048 | J4125 | No OS | 4GB | 128GB SSD | Clear | USB |
| E850204 | i3-9100TE | Windows 10 | 8GB | 128GB SSD | Clear | USB |
| E291517 | i3-9100TE | ChromeOS Flex | 8GB | 128GB SSD | Clear | USB |
| E850003 | i3-9100TE | No OS | 8GB | 128GB SSD | Clear | USB |
| E692244 | i5-9500TE | Windows 10 | 8GB | 128GB SSD | Clear | USB |
| E291723 | i5-9500TE | ChromeOS Flex | 8GB | 128GB SSD | Clear | USB |
| E692448 | i5-9500TE | No OS | 8GB | 128GB SSD | Clear | USB |

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 (0)16 70 45 00
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2024 Elo Touch Solutions, Inc. All rights reserved. 24052AES00128



22" I-Series 2 with Intel® AiO Interactive Display

| Model | i2 Models | i3 Models | i5 Models |
|---------------------------------------|---|---|---|
| Enclosure Color | Black | | |
| Display | 21.5" / 547 mm diagonal, active matrix TFT LED LCD | | |
| Aspect Ratio | 16:9 (standard) | | |
| Active Display Area (W x H) | 18.74" x 10.54" / 476.0 mm x 267.8 mm | | |
| Native (optimal) Resolution | 1920 x 1080 @ 60Hz | | |
| Touch Technologies | TouchPro® PCAP | | |
| Processor | Intel® Celeron® J4125 Processor (4M Cache, up to 2.7 GHz) | Intel Core i3-9100TE Processor (6M Smart Cache, up to 3.20 GHz by Intel Turbo Boost Technology 2.0) | Intel Core i5-9500TE Processor (9M Smart Cache, up to 3.60 GHz by Intel Turbo Boost Technology 2.0) Intel vPro™ Support |
| Chipset | N/A | Intel H310 Express | Intel Q370 Express |
| Graphics | Intel UHD Graphics 600 | Intel UHD Graphics 630 | |
| BIOS | AMI | | |
| Memory (RAM) | 4GB 2666MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 8GB on 2 slots) | 8GB 2666MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 32GB on 2 slots) | |
| Storage | 128GB M.2 SATA SSD 72 TBW | | |
| Operating Systems | No OS, Windows 10 IoT Enterprise LTSC 64-bit, Optional Windows 10 Professional 64-bit, ChromeOS Flex | | |
| USB Ports | 1 x USB 3.0; 4 x Micro USB for Elo peripherals | | |
| Ethernet Port | 1 x LAN RJ45 (Gigabit) | | |
| Wireless Connectivity | Wi-Fi 802.11 a/b/g/n/ac 2.4GHz and 5GHz and Bluetooth 5.0 | | |
| TPM | TPM 2.0 | | |
| AMT | N/A | Active Management Technology (Intel® AMT 11.0) Support. | |
| Audio | 2 x 2W Internal Speakers; 1 x 3.5mm headset jack | | |
| Colors | 16.7M | | |
| Brightness (typical) | LCD panel: 250 nits; TouchPro PCAP: 225 nits | | |
| Response Time Total (typical) | 14ms | | |
| Viewing Angle (typical) | Horizontal: 89°/178° total, Vertical: 89°/178° total | | |
| Contrast Ratio (typical) | 1000:1 | | |
| Control Buttons | Power | | |
| Power | External USB-C power supply brick; AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz; Maximum output power: 100W | | |
| Power Consumption | 39W | 77W | 83W |
| Dimensions | 20.7" x 12.57" x 2.07" / 525.9 mm x 319.2 mm x 52.6 mm | | |
| Shipping Box Dimensions | 24.61" x 7.72" x 17.2" / 625 mm x 196 mm x 437 mm | | |
| Weight | Unpacked: 11.5 lbs / 5.2 kg; Packaged: 15.4 lbs / 7 kg | | |
| Temperature | Operating: 0°C to 35°C / 32°F to 95°F; Storage: -20°C to 60°C / -4°F to 140°F | | |
| Humidity (non-condensing) | Operating: 20% to 80%; Storage: 5% to 95% (38.7°C max wet bulb temperature) | | |
| Energy Star Certified | Energy Star 7.1 | | |
| Regulatory approvals and declarations | UL/cUL, FCC, TUV, CE, CB, Mexico NOM, RCM/R-NZ, VCCI, Argentina S-Mark, CCC, UKCA Korea KCC for i5 Models only, India BIS for i2 Models only | | |
| Mounting Options | 75mm or 100mm VESA mount | | |
| Real-Time Clock | Replaceable CR2032 lithium battery for clock | | |
| Sealing | Touchscreen sealed to sub-bezel / Touchscreen sealed to LCD | | |
| Warranty | 3-year | | |
| Extended Warranties | 4 year: E819598; 5 year: E819795; 3 year + AUR: E820186; 4 year + AUR: E820388; 5 year + AUR: E820582 | | |
| MTBF | 50,000 hours demonstrated | | |
| Other Features | Serviceable internal components; Kensington lock | | |
| What's in the box | I-Series Touchcomputer, North America power cord, European power cord, Power adapter - 100W, cable cover locking screw, QIG | | |

Ordering Information

| Part Number | Processor | OS | Memory | RAM | Surface Treatment | Touch Interface |
|-------------|-----------|---------------|--------|-----------|-------------------|-----------------|
| E692640 | J4125 | Windows 10 | 4GB | 128GB SSD | Clear | USB |
| E291924 | J4125 | ChromeOS Flex | 4GB | 128GB SSD | Clear | USB |
| E692837 | J4125 | No OS | 4GB | 128GB SSD | Clear | USB |
| E850591 | i3-9100TE | Windows 10 | 8GB | 128GB SSD | Clear | USB |
| E292123 | i3-9100TE | ChromeOS Flex | 8GB | 128GB SSD | Clear | USB |
| E850387 | i3-9100TE | No OS | 8GB | 128GB SSD | Clear | USB |
| E693022 | i5-9500TE | Windows 10 | 8GB | 128GB SSD | Clear | USB |
| E292309 | i5-9500TE | ChromeOS Flex | 8GB | 128GB SSD | Clear | USB |
| E693211 | i5-9500TE | No OS | 8GB | 128GB SSD | Clear | USB |
| E948592 | i5-9500TE | Windows 10 | 8GB | 256GB SSD | Clear | USB |

Learn more about Elo at [EloTouch.com](https://elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 (0)16 70 45 00
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2024 Elo Touch Solutions, Inc. All rights reserved. 24052AES00128

