



”Modular 15.6"
all-in-one POS
system for everyone

Specifications – P5500

- **15.6" PCAP LCD with 350 nits and full HD resolution**
- **Powerful CPU: Intel Celeron 4305UE, Core i3-8145UE and Core i5-8265U**
- **Multiple ports, such as USB-C, pUSB 24V, RS232 etc.**
- **Mounting via optional 75 x 75 mm VESA mount possible**

		P5500
System	CPU	Intel Celeron 4305U (Intel Core i3-8145UE, Core i5-8265U, optional), fanless
	System memory	SO-DIMM DDR4, Dual-Channel, max. 32 GB
	Chipset	Intel Whiskey Lake platform
	Storage	2x M.2 (2280) slots
	Supported OS	Windows 10, Linux
Display	Graphics chip	Intel HD graphics
	LCD size	39.6 cm (15.6") LCD
	Max. resolution	1.920 x 1080 pixel (full HD)
	Brightness	350 nits, LED
	Touch screen	PCAP
	Tilt angle	0 to 90°
Interfaces	USB 2.0	4x
	USB 3.0	2x
	USB C	2x (DP & USB)
	Powered USB	1x (24 V)
	Serial / COM (RJ45)	3x (RJ45)
	Parallel	-
	LAN	1x (Gigabit)
	Graphics port	USB C (DP)
	Cash drawer port	1x (12V/24V, RJ11)
PSU	Power adapter	90 watts
	Dimensions (WxDxH)	365.3 x 40.3 x 220.4 mm (without stand)
Other	Weight	4 kg
	Operating temperature	0 °C – 40 °C
	Certification	CE, RoHS
	Mounting options	VESA 75 x 75 mm
Options	MSR	Yes
	Customer display	Yes (2 x 20 characters integrated)
	Customer-facing screen	Yes (8", 9.7", 15.6")
	Barcode scanner	Yes (1D, 2D)
	Waiter's lock	Yes (iButton)
	RFID	TBD
	Colour	Black / silver

*factory default

Your partner