

GRANIT™ ULTRA 2100iXR

Ultra-Rugged Area-Imaging Expanded Range Scanner

Honeywell Granit Ultra scanners expand capabilities and define the next generation of ultra-rugged scanning.

ULTRA SCAN PERFORMANCE

For a scanner to optimize productivity, it should read and transmit common barcodes nearly as fast as the user can pull the trigger. Granit Ultra is engineered to do just that. Damaged or low quality printed barcodes can cause many scanners' pace to decrease, or even force cumbersome (and error-prone) manual data entry. To maximize throughput, scanners must successfully compensate for poor code quality before scan delays put pressure on production.

Granit Ultra integrates high speed processing, AI algorithms, and decoding enhancements to result in an average 45% scanning speed increase vs. Granit XP*, enabling improved productivity. XR models scan rapidly from at or near contact up to 33' for 100 mil Code 39 rack labels, or nearly 6' (1.8m) with UPC codes, enabling reduced walking or stooping to read codes at greater distances for improved ergonomics and productivity.

ULTRA DURABILITY

In modern warehouse, distribution center, and manufacturing environments, any scanner must be durable enough to survive harsh operating conditions and powerful enough to capture and transmit barcode data without slowing workflows. Under exactly that kind of rough treatment, Honeywell Granit Ultra is ready to deliver. 10' drops from fork trucks, docks, and picking trucks, 7,500 tumbles from 3'/1m (typical working height), and wide operating temperatures from deep freezers to the heat of summer are no problem.

But great specs alone are meaningless if there are other weak links in the chain. For instance, customers often cite scratched and broken scan windows as a frequent failure point in competitive scanners. Honeywell Granit Ultra's small, deeply recessed, scratch- and impact-resistant scan window is designed to address this, helping ensure that the electronics and optics remain IP65/68 protected. Scanner cables are another commonly reported failure point for other brands. Honeywell's rigorous specifications on scanner cables (including 500K cycle flex, weighted pull, and even deep freezer specific versions tested to 300K flexes at a frigid -30C/-22F) ensure that each link in the data chain offers premium reliability.

To learn more about how Granit Ultra is ready to improve your operations, contact your Honeywell representative or partner today.



Granit™ Ultra 2100iXR Scanner

*Honeywell standard benchmarking testing conducted on Granit Ultra SR and XR models vs. Granit XP on 6 collections of reference barcodes.

ULTRA EASE OF USE

Ready to operate right out of the box for many applications, Granit offers easy custom configuration in the time it takes to scan a barcode. Comfortable ergonomic design compliments the human hand and is readily compatible with the full range of users. Crisply focused illumination intuitively defines the field of view, and a sharp aimer defines the focal point and can be used for precise code targeting in applications where many barcodes are located in close proximity. And for workflows better expedited by reading many barcodes at once, Granit can read multiple codes in the field of view, organizing and outputting the data in a predefined order using Honeywell's Data Format Editor.

FEATURES AND BENEFITS



BUILT TO LAST

Built to survive harsh treatment including 3m (10ft) drops, 7500 1m (3.3ft) tumbles, operating temperatures from -30°C to 50°C (-22°F to 122°F), and IP65/68 sealing, Granit Ultra is engineered to reduce service costs and increases device uptime.



FAST SCANNING

Granit Ultra provides rapid scanning, even on damaged and low quality barcodes. High quality barcodes transmit faster than ever.



CLOSE PROXIMITY

XR model is ideally suited to near and mid-field scanning operations on 1D and 2D barcodes. For arms-length only scanning, or to read even longer reading distances, refer to SR or XLR models in the Granit family.



HOLISTIC SOLUTION

The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

TECHNICAL SPECIFICATIONS

TABLE 1. MECHANICAL

| Characteristic | Parameter |
|------------------------|---|
| Dimensions (L x W x H) | 194.8mm x 75.8mm x 139.5mm (7.7 in x 3.0 in x 5.5 in) |
| Weight – Corded | 330g (11.64 oz) |
| User Indicators | Good decode LEDs, Beeper (adjustable tone and volume), Vibration (adjustable) |

TABLE 2. ELECTRICAL

| Characteristic | Parameter |
|--|---|
| Input Voltage | 4.4 to 5.5 VDC |
| Operating Power (USB 2.0) – Corded | 2.15W (430mA @ 5VDC) RMS |
| Operating Power (Other interfaces) Corded: | 2.75W (550mA @ 5VDC) RMS |
| Standby Power – Corded | 0.875W (175mA @ 5VDC) RMS |
| Host System Interfaces | USB, RS-232 TTL (cables available to convert for +/-12V True use), Keyboard Wedge |

GRANIT ULTRA 2100ISR Technical Specifications

| TABLE 3. ENVIRONMENTAL | |
|---------------------------------|---|
| Characteristic | Parameter |
| Operating Temperature – Corded* | -30°C to 50°C (-22°F to 122°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158°F) |
| Humidity | Up to 95% relative humidity, non-condensing |
| Drop | 3m (10 ft): MIL-STD-810G, 25C (77°F), 55% RH |
| | 2.5m (8 ft): 20 drops from -30°C to 50°C (-22°F to 122°F), uncontrolled RH |
| | 2m (6.5 ft): 50 drops from -30°C to 50°C (-22°F to 122°F), uncontrolled RH |
| Tumble | 7,500 1m (3.3ft) tumbles |
| Environmental Sealing: Scanner | IP65 and IP68 |
| Light Levels | 0 to 100,000 lux (9,290 foot-candles) |
| ESD | Up to +/-20KV air discharge, +/-8kV contact discharge, +/-8kV indirect coupling plane |

| TABLE 4. SCAN PERFORMANCE | |
|------------------------------------|---|
| Characteristic | Parameter |
| Scan Pattern | Area imager (1280 × 1080 pixel array) |
| Illumination | Yellow-green LED |
| Aimer | 520nm laser |
| Motion Tolerance | Up to 4 m/s (157 in/s) |
| Scan Angle | Horizontal: 42°, Vertical 36° |
| Print Contrast | As low as 15% |
| Minimum Barcode Element Resolution | 2.5 mil 1D, 5 mil 2D |
| Roll, Pitch, Skew | +/-360°, 65°, 65° |
| Decode Capabilities | Reads standard 1D, PDF, 2D, Postal, Digimarc, DOT Code, and OCR symbologies |
| Image Capture | Up to 109PPI on an A4 document |
| Warranty – Scanner | Three year factory warranty |

| TABLE 5. TYPICAL PERFORMANCE** | | | | |
|--------------------------------|--------------------------|------------------------|-----------------------------|------------------------|
| Symbology | Standard Range - Typical | | Standard Range - Guaranteed | |
| | Near Distance (mm [in]) | Far Distance (mm [in]) | Near Distance (mm [in]) | Far Distance (mm [in]) |
| 5 mil C39 | 10 [0.39] | 269 [10.59] | 21 [0.83] | 252 [9.92] |
| 10 mil C128 | 0 [0.0] | 1503 [59.17] | 0 [0.0] | 1455 [57.28] |
| 13 mil UPC | 0 [0.0] | 1780 [70.08] | 0 [0.0] | 1586 [62.44] |
| 20 mil C128 | 0 [0.0] | 2812 [110.71] | 0 [0.0] | 2621 [103.19] |
| 100 mil C39 | 0 [0.0] | 10848 [427.09] | 0 [0.0] | 9242 [363.86] |
| 6.7 mil PDF417 | 14 [0.55] | 243 [9.57] | 23 [0.91] | 233 [9.17] |
| 10 mil DataMatrix | 5 [0.20] | 261 [10.28] | 14 [0.55] | 247 [9.72] |
| 20 mil QR Code | 0 [0.0] | 1464 [57.64] | 0 [0.0] | 1415 [55.71] |
| 100 mil DataMatrix | 0 [0.0] | 5329 [209.80] | 0 [0.0] | 4724 [185.98] |

*With industrial-grade cable ordered separately.

**Performance may be impacted by barcode quality and environmental conditions.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

ADDITIONAL INFORMATION

- Integration Manual is available upon request; contact your Honeywell representative
- For a listing of common compliance approvals and certifications, visit our [website](#).

NOTICE

MISUSE OF DOCUMENTATION

- The information presented in this datasheet is for reference only. Do not use this document as a product installation guide
- An installation manual is available by request on our [website](#). Please contact your Honeywell sales representative

For more information

automation.honeywell.com

Honeywell Industrial Automation

855 South Mint Street
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Granit is a trademark or registered trademark of Honeywell International Inc.

All other trademarks are the property of their respective owners.

Granit Ultra 2100iXR EN LTR | 1 | 11/24
© 2024 Honeywell International Inc. All Rights Reserved

