



MOBILE PRINTER MP-B21L SERIES

2" Mobile Receipt Printer

- High-speed printing
- Compact design
- Printing of labels and receipt paper
- For use in harsh environments
- Different usage scenarios
- Option cradle for charging

MP-B21L SERIES

Mobile Printer



Measuring Instrument



PDA/Smart Device



Barcode



Portable Printer



Label



Medical Equipment

Made for

iPod iPhone iPad

MP-B21L



Model		MP-B21L
Printing	Method	Thermal line dot printing
	Number of dots/line	384
	Resolution (dots/mm)	8
	Paper width (mm)	58 ^{*1}
	Printing width (mm)	48
	Speed (mm/sec) max	153
	Outside diameter of paper roll (mm) max	Ø 51
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of Paper	Roll paper, Label roll paper	
Character type	Code page (17 pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character	
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128 PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, Aztec Code	
Power supply (V)	Li-Ion Battery	
Communication interface	USB, Bluetooth [®] W-LAN ^{*2}	
Command	ESC/POS [™] conformity, ZPL II [™] conformity, CPCL conformity	
Cutting	Tear bar	
Falling resistance	1.8m ^{*3}	
IP rating	IP54 ^{*3}	
Operating temperature (°C)	-20 to 55	
Service life (km)	50 ^{*2}	
Dimensions (W×D×H mm)	90 × 126 × 58 ^{*5}	
Mass (g)	Approx. 370 ^{*6}	
Standard	FCC, CE, VCCI	
Bundled item	AC dapter, Belt clip, Battery, USB cable, Sample roll paper	
Option	Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case	
Software	Windows [®] : Printer Driver / OPOS / POS for .NET / Utility / Layout Editor Android [™] : Printer Class Library / URL Print Agent / Layout Editor / MAUI SDK / Utility iOS: Printer Class Library / URL Print Agent / Layout Editor / MAUI SDK / Utility	

^{*1}Please inquire about support for narrow paper ^{*2}Selected model ^{*3}This number is test result based on SII procedures, not guaranteed value ^{*4}Use recommended thermal papers ^{*5}Excluding protrusion ^{*6}With battery, without paper roll

ESC/POS[™]: Registered trademark of SEIKO EPSON CORP.
Windows[®] is the registered trademark of Microsoft Corporation(USA).
Android[™] is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH

Siemensstraße 9, 63263 Neu-Isenburg, Germany
phone: +49-6102-297-0 · e-mail: info@seiko-instruments.de
www.seiko-instruments.de