

## MOBILE PRINTER MP-B20 SERIES

## 2" Mobile Receipt Printer

- Very small and lightweight
- 1,5 meters drop rate
- USB style battery charger

- 80mm/s printing speed
- Belt Clip included
- optional cradle

## **MP-B20 SERIES**

## **Mobile Printer**











Portable Printer









	MP-B20
Method	Thermal line dot printing
Number of dots/line	384
Resolution (dots/mm)	8
Paper width (mm)	58 <sup>.0</sup>
Printing width (mm)	48
Speed (mm/sec) max	80
Outside diameter of paper roll (mm) max	Ø 40
Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
er	Roll paper
pe	Code page (17 pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128 PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
y (V)	Li-lon Battery
tion interface	USB, Bluetooth*
	4K bytes
	ESC/POS™ conformity
	Tear bar
tance	1.5m <sup>4</sup>
emperature (°C)	-10 to 50
km)	50* <sup>2</sup>
(W×D×H mm)	79.0 × 110.0 × 44.0*3
	Approx. 180* <sup>4</sup>
	FCC, CE, VCCI
n	USB cable, Battery, Belt clip
	Cradle for charging
	Printer driver, Windows®, Android™(SDK), iOS(SDK)
	Number of dots/line Resolution (dots/mm) Paper width (mm) Printing width (mm) Speed (mm/sec) max Outside diameter of paper roll (mm) max Character matrix (H×W mm) Character dimensions (H×W mm) er  pe  (y (V) tion interface  tance tance tance (°C) km) (W×D×H mm)

<sup>&</sup>quot;1 This number is test result based on SII procedures, not guar anteed value. \*2 using specified thermal paper \*3 Excluding protrusion \*4 with battery, without paper roll

ESC/POS\*: Registered trademark of SEIKO EPSON CORP.
Windows\* is the registered trademark of Microsoft Corporation(USA).
Android\* is a trademark of Google Inc.
IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.

