




MOBILE PRINTER MP-B30L SERIES

3" Mobile Label and Receipt Printer

- Ultra small & Lightweight
- 1,8m (6 feet) drop rate
- IP54 protection
- 130mm/s max print speed
- NFC for easy BT pairing
- BT or WiFi and USB interface
- Optional cradle for charging

MP-B30L SERIES

Mobile Printer



Measuring Instrument



PDA/ Smart Device



Barcode



Portable Printer



Label



Medical Equipment

Made for

iPod iPhone iPad



MP-B30L
Belt Clip



Model		MP-B30L
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 ⁺⁰ ₋₁ / 76.2 ⁺⁰ ₋₁ / 58 ⁺⁰ ₋₁
	Printing width (mm)	72
	Printing Speed (mm/sec) max	130
	Outside diameter of paper roll (mm) max	∅ 51
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of Paper	Roll paper, Label roll paper	
Character type	Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character	
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128,PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, AZTEC	
Power supply	Li-Ion Battery	
Communication interface	USB, Bluetooth®, W-LAN ^{*1}	
Input buffer	4K bytes	
Command	ESC/POS™ conformity, ZPL II™ conformity, CPCL conformity	
Cutting method	Tear bar	
Falling resistance	1.8m ^{*2}	
IP rating	IP54 ^{*2}	
Operating temperature (°C)	-20 to 55	
Service life: Abrasion resistance (km)	50 ^{*3}	
Dimensions (W×D×H mm)	105 x 126 x 58 ^{*4}	
Mass (g)	395 ^{*5}	
Standard	FCC, CE, VCCI	
Bundled item	AC adapter, Battery, USB cable, Belt clip	
Option	Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case	
Software	Printer driver, OPOS, POS for .NET, Windows® CE(SDK), Android™(SDK),iOS SDK, Xamarin SDK, URL Print Agent	

^{*1} Selected model. ^{*2} This number is test result based on SII procedures, not guaranteed value. ^{*3} Use recommended thermal papers. ^{*4} Excluding protrusion ^{*5} with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP.
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH

Siemensstraße 9, 63263 Neu-Isenburg, Germany
phone: +49-6102-297-0 · e-mail: info@seiko-instruments.de
www.seiko-instruments.de