



# LABEL AND RECEIPT PRINTER SLP720RT SERIES (LINER-FREE)

**2" compact and powerful solution for liner-free label, standard label and receipt printing.**


- Works with Restick Liner-free labels, receipt paper and lined labels
- 102mm Paper roll outside diameter
- 200mm/s printing speed
- Compact design (90x200x141mm)
- Partial and full paper cut option
- Label taken sensor
- Efficient paper saving options
- Multiple Software incl. Label editor available

# SLP720RT SERIES

Label / Receipt Printer



POS/ECR



Measuring Instrument



Barcode



KIOSK System



Medical Equipment



Gaming

Made for

iPod iPhone iPad

SLP720RT



Model		SLP720RT
Printing	Method	Thermal line dot printing
	Resolution (dpi)	203 (8 dots/mm)
	Paper width (Printing width) (mm)	Restick liner-free label, Receipt paper : 40 (36) , 58 (54) Label (Liner width) : 31 to 58
	Speed (mm/sec) max	200
	Outside diameter of paper roll (mm) max	Ø 102
	Character matrix (H×W dots)	24 X 12, 24 X 24, 16 X 8, 16 X 16
	Character size (H×W mm)	3.0 X 1.5, 3.0 X 3.0, 2.0 X 1.0, 2.0 X 2.0
Paper	Media Type	Restick liner-free label, Receipt paper, Label with liner. Roll paper (Drop in)
	Top margin (mm) min	4
	Paper sensor	Out of paper sensor, Timing mark sensor, Label taken sensor
Character type		Code page (18Pages), International character, Optional font, Downloaded character, JIS 1&2 Level Kanji, Special character, User-defined character
Barcode		UPC-A/E, JAN(EAN)8/13, ITF, CODABAR, Code39, Code93, Code128, QR code, PDF417, Maxi code, Data matrix, GS1 Databar
Power supply		Specified AC adapter, External power (DC24±10%)
Communication Interface		USB, Ethernet+USB, Wireless LAN
Command		ESC/POS™ (Standard mode) conformity
Cutting	Method	Slide type
	Cutting type	Full cut, Partial cut (Leave center point)
Operating temperature (°C)		5 to 45
Service life	Paper cutting (cut)	Restick liner-free label, Receipt paper: 1,000,000 *1
Dimensions (W×D×H mm)		90 x 200 x 141 *2
Mass (g)		Approx. 1100
Standard		FCC, CE, UKCA, VCCI
Software		Windows® : Printer Driver, OPOS Driver, POS for .Net Driver / SDK / Utility (Label editor etc.) Android™ : SDK / Utility (Label editor, PDF print from Web etc.) iOS : SDK / Utility (Label editor, PDF print from Web etc.)

\*1 Use recommended thermal papers \*2 Excluding protrusion

ESC/POS™: Registered trademark of SEIKO EPSON CORP.  
Windows® is the registered trademark of Microsoft Corporation(USA).  
Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH

Siemensstraße 9, 63263 Neu-Isenburg, Germany  
phone: +49-6102-297-0 · e-mail: info@seiko-instruments.de  
www.seiko-instruments.de